

PFAFF

fine sewing

1183-712/02 333-712/02

Tacking and basting work



tüv
CERT
DIN EN ISO 9001:1994
QA 05 100 1002



Tacking and basting of jackets, overcoats, ladies' jackets etc.

Features:

- Low-vibration, low-noise running
- Easy operation with S1 control panel
- Easy drawing of the thread when shifting the workpiece
- Simple processing of materials up to 12 mm thick (by PFAFF 333: 18 mm), depending on the needle system used
- The automatic needle reversing mechanism provides more clearance for easy loading
- Reliable sewing start after thread trimming due to the solenoid-controlled thread tension
- Sewing head auto select system to recognize the pre-set parameters for service purposes
- Integrated bobbin thread winder

Features 1183-712:

- Integrated servo-motor
- High flexibility due to the adjustable needle bar stroke (36 mm).
One machine for all material thicknesses
- Up to 13 mm presser foot clearance (with 36 mm needle bar stroke)
- Knife/catcher change for the thread trimming device without readjustment

Features 333-712:

- First-rate handling due to the new cylindrical bed cover
- The 18 mm foot lift makes it easy to sew even thick padding

Available types:

Cylinder bed jumper baster:

PFAFF 333-712/02-6/01-900/51 AS
with thread trimmer, small hook and
integrated Servo-Motor

PFAFF 333-G-712/02-6/01 BS
with large hook

Flat bed jumper baster:

PFAFF 1183-712/02-6/01-900/24 BS
with thread trimmer

Specifications:

Stitch type:
301

Max. speed:
1183-712
max. 1200/min
333-712
max. 1000/min

Needle system:
134-35R or 190

Needle size:
(Nm in 1/100 mm)
80-100

This machine is equipped with finger-guard, belt- and take-up lever guards as standard.

Subject to changes in design, weight and dimensions.

For further information please contact our Product Management department
Tel.: ++49-631-200-1330
Fax: ++49-631-200-1393