

# PFAFF

fine sewing

# 422 1422

Two-needle, lockstitch special high-speed seamer  
with compound feed



**Single or two-needle seams on light to medium fabrics e.g. shirts, blouses, jeans and leisurewear etc.**

## **422**

For sewing delicate materials e.g. microfiber and silk with the A-version.

## **1422**

Large vertical sewing hooks.  
Large bobbin volume.

## **1422 with subclass -720/04**

For setting pockets onto sportswear, leisurewear and work clothing.

- Perfect corner stitching due to left or right disengageable needles.
- Single- and two needle operation at full speed.
- Needles can be engaged and disengaged even at maximum speed.
- Precise positioning of the starting stitches with the "stitch placement" key.

## **Accessories**

- Thread trimmer -900/81
- Backtacking facility -911/35
- Presser foot lifter -910/04
- Pneumatic thread trapper -906/09 (optional).
  - No knotting of loose threads.
  - Starting threads are not pulled out of the needle.



## **Specifications**

- Needle gauge: 3.2-12.0 mm, depending on accessories installed

### **422**

- Versions: A and B
- Max. speed in s.p.m.: 5000
- Max. stitch length: 4.5 mm
- Sewable thread: up to 40/3 synth.

### **1422**

- Versions B and C
- Max. speed in s.p.m.: 4000
- Max. stitch length: 6 mm
- Sewable thread: up to 30/3

### Hotlines:

Technical service : ++49-175/2243-101

Application consultancy : ++49-175/2243-102

Spare-parts hotline : ++49-175/2243-103



## **PFAFF Industrie Maschinen AG**

- Postfach 3020  
D-67653 Kaiserslautern
- Königstr. 154  
D-67655 Kaiserslautern

Telefon: ++49-631/200-0

Telefax: ++49-631/17202

Internet: [www.pfaff-industrial.com](http://www.pfaff-industrial.com)